



## BL-450 black line



**450Watt**

**MLO system, DBS, Drive.**  
**Switch Mode Power Supply, light weight and compact dimensions.**

**BL-450 HEAD** is dedicated to those who prefer reliable and efficient constructions, easy to control on the shortest track to optimal sound.

Wide dynamic range, selective sound with high fidelity in reproduction of the instrument are its most significant virtues. As the whole Taurus line also BL-450 HEAD is equipped with our unique intuitional MLO system to find the right sound within seconds.

The amp is powered by outstandingly efficient high energy Switching Mode Power Supply which ensures extremely high dynamics and power in a light weight and compact cabinet.



## SPECIFICATIONS:

**Power output:** 450W RMS / 4ohm , 300W RMS / 8ohm

**Inputs:** passive & active

### Controls:

**GAIN** control with overload indicator.

**VOLUME** control

### Tone:

**BASS** and **TREBLE** equalizer with "MLO-system" (Middle-range Level Optimization).

Triple **BASS-switch** to reduce or boost low frequency [**DBS-cut/OFF/DBS-boost**]

Triple **TREBLE-switch** to reduce or boost high frequency [**CUT/OFF/PRESENCE**]

**PARAMETRIC EQUALIZER** for precise control of middle range (120Hz-4kHz)

**PUNCH** button - increases sonic expression

### Other features:

**MUTE** button

**CLIP** power amp indicator

**PEAK** preamp overload indicator

**Effect loops:** **SEND / RETURN** (jack 1/4 inch)

**Outputs:** XLR balanced **LINE** output with **PRE/POST** switch and **GROUND LIFT** circuit switch, **TUNER**, **SPEAKERS** (combo speakon/jack)

**Protections:** short circuit, thermal overload, power overload

Forced cooling system with electronic efficiency control

**Casing dimensions:** [H x W x D] 66x380x180mm

**Overall dimensions:** [H x W x D] 66x380x205mm

**Weight:** 3.3 kg

# DESIGNED BY MUSICIANS FOR MUSICIANS

# Taurus

[www.taurus-amp.pl](http://www.taurus-amp.pl)  
[info@taurus-amp.pl](mailto:info@taurus-amp.pl)

**Box Electronics** ul. Cieszyńskiego 4  
81-881 Sopot, POLAND  
tel./fax +48 (058) 550 66 46, 551 90 05